



Safety Data Sheet

SO SURE General Purpose Enamel, Green 14064

Revision Date:
13 August, 2026

Section 1. Identification

Product identifier**Product Identity**

SO SURE General Purpose Enamel, Green 14064

Other means of identification

TA2|LHB Part Number: 01D4-141
National Stock Number: 8010-01-505-1970
CAGE Code: 0FTT5
Contract Number: GS-10F-40278

Relevant identified uses of the substance or mixture and uses advised against

See Product Label

Details of the supplier of the safety data sheet**Company Name**

LHB Industries
8833 Fleischer Place
Berkeley, MO 63134

Emergency**24 hour Emergency Telephone No.**

(800) 633-8253 (PERS)

Customer Service:

(314) 423-4333

Section 2. Hazard(s) identification

Classification of the substance or mixture under OSHA's Hazard Communication Standard (1910.1200) revised 2024 (GHS revision 7).

Flammable Aerosol, category 1;H222
H229

Extremely flammable aerosol.
Pressurized container: May burst if heated.

Serious eye damage / eye irritation, category 2A;H319
Specific target organ toxicity, Single exposure category 3;H336

Causes serious eye irritation.
May cause drowsiness or dizziness.

Specific target organ toxicity, repeated exposure category 1;H372

Causes damage to organs through prolonged or repeated exposure. Specific Target Organs: (central nervous system)

Simple Asphyxiant

May displace oxygen and cause rapid suffocation.

Label elements

Danger



Safety Data Sheet

SO SURE General Purpose Enamel, Green 14064

Revision Date:
13 August, 2026

H222 Extremely flammable aerosol.

H229 Pressurized container: May burst if heated.

H319 Causes serious eye irritation.

H336 May cause drowsiness and dizziness.

H372 Causes damage to organs through prolonged or repeated exposure.

May displace oxygen and cause rapid suffocation.

[Prevention]

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No Smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Pressurized container: Do not pierce or burn, even after use.

P260 Do not breathe dust, fume, mist, vapors or spray.

P262 Do not get in eyes, on skin, or on clothing.

P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves, eye protection, and face protection.

[Response]

P301+310 IF SWALLOWED: Immediately call a POISON CENTER, doctor or physician.

P304+340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312 Call a POISON CENTER, doctor or physician if you feel unwell.

P314 Get medical advice or attention if you feel unwell.

P331 Do NOT induce vomiting.

P337+313 If eye irritation persists: Get medical advice or attention.

[Storage]

P403+233 Store in a well ventilated place. Keep container tightly closed.

P405 Store locked up.

P410+412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C, 122 °F.

[Disposal]

P501 Dispose of contents or container in accordance with local and national regulations.

Other hazards

May displace oxygen and cause rapid suffocation.

This product contains no PBT/vPvB/vPvM chemicals.

This product contains no endocrine disrupting chemicals.

Does NOT contain component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS) per the US EPA PFASMASTER combined list of PFAS chemicals.



Safety Data Sheet

SO SURE General Purpose Enamel, Green 14064

Revision Date:
13 August, 2026

Section 3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the OSHA's Hazard Communication Standard (1910.1200) revised 2024 (GHS revision 7).

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Acetone CAS Number: 67-64-1 Synonyms: 2-Propanone, Dimethyl ketone, Dimethylformaldehyde, Propanone	10 - 30	Flammable Liquid, category 2;H225 Serious eye damage / eye irritation, category 2;H319 Specific target organ toxicity, Single exposure category 3;H336	No data available
Propane CAS Number: 74-98-6 Synonyms: No available information	10 - 30	Flammable Gas, category 1A;H220 Liquified Gas;H280 Simple Asphyxiant	No data available
Naphtha (petroleum), hydrotreated light CAS Number: 64742-49-0 Synonyms: Aliphatic Hydrocarbon	7 - 13	Aspiration hazard, category 1;H304 Flammable Liquid, category 1;H224	No data available
Butane CAS Number: 106-97-8 Synonyms: No available information	7 - 13	Flammable Gas, category 1A;H220 Liquified Gas;H280 Simple Asphyxiant	No data available
Isobutane CAS Number: 75-28-5 Synonyms: 2-methylpropane, Propane, 2-methyl-	3 - 7	Flammable Gas, category 1A;H220 Gas under pressure;H280	No data available
N-Butyl Acetate CAS Number: 123-86-4 Synonyms: Acetic acid, butyl ester, Butyl acetate, n-Butyl axetat	3 - 7	Flammable Liquid, category 3;H226 Specific target organ toxicity, Single exposure category 3;H336	No data available
Stoddard solvent CAS Number: 8052-41-3 Synonyms: White spirits	1 - 5	Specific target organ toxicity, repeated exposure category 1;H372 Aspiration hazard, category 1;H304	No data available
2-Methoxy-1-Methylethyl Acetate CAS Number: 108-65-6 Synonyms: 1-Methoxy-2-propyl acetate, Propylene glycol monomethyl ether acetate	1 - 5	Flammable Liquid, category 3;H226	No data available

The actual concentration or concentration range is withheld as a trade secret.

*PBT/vPvB - PBT, vPvM or vPvB-substance.

The full texts of the phrases are shown in Section 16.

Section 4. First aid measures

Description of first aid measures

General

In all cases of doubt, or when symptoms persist, seek medical attention.
Never give anything by mouth to an unconscious person.

Inhalation

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious, place in the recovery position and obtain immediate medical attention. Give nothing by mouth.

Eyes

Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.



Safety Data Sheet

SO SURE General Purpose Enamel, Green 14064

Revision Date:
13 August, 2026

Skin	Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser.
Ingestion	DO NOT INDUCE VOMITING. Give nothing by mouth. Get immediate medical attention.
Most important symptoms and effects, both acute and delayed	
Overview	EFFECTS OF OVEREXPOSURE: Overexposure may result in light-headedness, staggering gait, giddiness, and possible nausea. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. May cause eye and skin irritation. SIGNS AND SYMPTOMS OF OVEREXPOSURE: Headache, dizziness, nausea, and loss of coordination are indications of excessive exposure to vapors or spray mists. Redness and itching or burning sensation may indicate eye or excessive skin exposure. MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: Pre-existing respiratory, skin, and eye disorders. No chronic toxicity or long term toxicity information available. Treat symptomatically. Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation, and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage. See section 2 for further details.
Inhalation	May cause drowsiness or dizziness.
Eyes	Causes serious eye irritation.

Section 5. Fire-fighting measures

Extinguishing media

Recommended extinguishing media; alcohol resistant foam, CO₂, powder, water spray.

Unsuitable extinguishing media: Do not use; water jet.

Special hazards arising from the substance or mixture

Hazardous decomposition: Oxides of Carbon

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No Smoking.

Do not spray on an open flame or other ignition source.

Pressurized container: Do not pierce or burn, even after use.

Do not breathe dust, fume, mist, vapors or spray.

Do not get in eyes, on skin, or on clothing.

Advice for fire-fighters

FIRE FIGHTING EQUIPMENT: Fire fighters should wear full protective equipment, and have self-contained breathing apparatus available.

SPECIAL PROCEDURES: Use water to cool containers exposed to a fire.

Self-extinguishing. Does not hold a flame

ERG Guide No. 126



Safety Data Sheet

SO SURE General Purpose Enamel, Green 14064

Revision Date:
13 August, 2026

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Put on appropriate personal protective equipment (see section 8).

Use good personal hygiene practices. Wash hands before eating, drinking, smoking, or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

Environmental precautions

Do not allow spills to enter drains or waterways.

Methods and material for containment and cleaning up

Ventilate the area and avoid breathing vapors. Take the personal protective measures listed in section 8.

Contain and absorb spillage with non-combustible materials e.g. sand, earth, and vermiculite. Place in closed containers outside buildings and dispose of according to the Waste Regulations.

Section 7. Handling and storage

Precautions for safe handling

Handle containers carefully to prevent damage and spillage.

Keep out of reach of children. Keep away from heat, sparks, and open flame. Vapors will accumulate readily and may ignite explosively. During use and until all vapors are gone: keep area ventilated- DO NOT SMOKE- Extinguish all flames, pilot lights, and heaters- Turn off stoves, electric tools and appliances, and any other source of ignition. Consult NFPA Code. Use approved Bonding and Grounding procedures. Contents under pressure. Do not puncture, incinerate, or expose to temperatures above 120F. Heat from sunlight, radiators, stoves, hot water, and other heat sources could cause container to burst, do not take internally.

See section 2 for further details. - [Prevention]

Conditions for safe storage, including any incompatibilities

Incompatible materials: Strong acids and oxidizing materials

See section 2 for further details. - [Storage]

Specific end use(s)

See Product Label

Section 8. Exposure controls / personal protection

Control parameters

Exposure Limits

CAS No.	Ingredient	Source	Value
67-64-1	Acetone	OSHA	1000 ppm, 2400 mg/m ³
		ACGIH	TWA: 250 ppm STEL: 500 ppm
		NIOSH	250 ppm (590 mg/m ³) TWA
74-98-6	Propane	OSHA	1000 ppm, 1800 mg/m ³
		ACGIH	(D) Simple Asphyxiant - (EX) Explosion hazard



Safety Data Sheet

SO SURE General Purpose Enamel, Green 14064

Revision Date:
13 August, 2026

		NIOSH	TWA 1000 ppm (1800 mg/m ³)
75-28-5	Isobutane	OSHA	No Established Limit
		ACGIH	TWA: 1000 ppm (EX) Explosion hazard
		NIOSH	TWA 800 ppm (1900 mg/m ³)
106-97-8	Butane	OSHA	No Established Limit
		ACGIH	TWA: 1000 ppm (EX) Explosion hazard
		NIOSH	TWA 800 ppm (1900 mg/m ³)
108-65-6	2-Methoxy-1-Methylethyl Acetate	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
123-86-4	N-Butyl Acetate	OSHA	150 ppm, 710 mg/m ³
		ACGIH	TWA: 50 ppm STEL: 150 ppm
		NIOSH	TWA 150 ppm (710 mg/m ³) STEL: 200 ppm (950 mg/m ³)
8052-41-3	Stoddard solvent	OSHA	500 ppm, 2900 mg/m ³
		ACGIH	TWA: 100 ppm
		NIOSH	TWA 350 mg/m ³ C 1800 mg/m ³ [15-minute]
64742-49-0	Naphtha (petroleum), hydrotreated light	OSHA	No Established Limit
		ACGIH	TWA: 100 ppm
		NIOSH	No Established Limit

Exposure controls

Respiratory

If personal exposure cannot be controlled to below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section 2. When sanding or abrading the dried film, wear a dust/mist respirator approved by NIOSH/MSHA for dust that may be generated from this product, underlying paint, or the abrasive.

Eyes

Use safety glasses with side shields or chemical goggles. If exposure causes eye discomfort, use a full-face respirator.

Skin

Wear overalls to keep skin contact to a minimum. Chemical resistant gloves may be needed for long term skin exposure.

Engineering Controls

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits suitable respiratory protection must be worn.

Other Work Practices

Use good personal hygiene practices. Wash hands before eating, drinking, smoking, or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details.

Section 9. Physical and chemical properties

Information on basic physical and chemical properties

Physical State

Liquid

Color

Green



Safety Data Sheet

SO SURE General Purpose Enamel, Green 14064

Revision Date:
13 August, 2026

Odor	Solvent
Odor threshold	Not Available
Melting point / freezing point	Not Determined
Initial boiling point and boiling range	Not Determined
Flammability (solid, gas)	Not Applicable
Upper/lower flammability or explosive limits	Lower Explosive Limit: Not Determined Upper Explosive Limit: Not Determined
Flash Point	-156°F (propane)
Auto-ignition temperature	Not Determined
Decomposition temperature	Not Determined
pH	Not Determined
Kinematic viscosity	Not Determined
Solubility in Water	Insoluble
Partition coefficient n-octanol/water (Log Kow)	Not Available
Vapor pressure (Pa)	Not Determined
Relative Density	0.735
Vapor Density	Not Determined
% Volatile (by volume)	87.83 % (by volume)
Evaporation rate (Ether = 1)	Not Determined
VOC Content	526 g/L (4.39 lbs/gal) (Minus exempt solvents and water)
Maximum Incremental Reactivity	0.70
HAPS (lbs/gal)	0.0
HAPS (lbs/gal of Solids)	0.0
HAPS (lbs/lb of Solids)	0.0
Other information	
No other relevant information.	

Section 10. Stability and reactivity

Reactivity

Hazardous Polymerization will not occur.

Chemical stability

Stable under normal circumstances.

Possibility of hazardous reactions

No data available.

Conditions to avoid

Do not expose to heat or store at temperature above 120°F.

Incompatible materials

Strong acids and oxidizing materials

Hazardous decomposition products

Oxides of Carbon



Safety Data Sheet

SO SURE General Purpose Enamel, Green 14064

Revision Date:
13 August, 2026

Section 11. Toxicological information

Acute toxicity

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation, and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
Acetone - (67-64-1)	5,800.00, Rat - Category: NA	7,426.00, Rabbit - Category: NA	76.00, Rat - Category: NA	50.10, Rat - Category: NA	No data available.
Propane - (74-98-6)	No data available.	No data available.	658.00, Rat - Category: NA	No data available.	No data available.
Naphtha (petroleum), hydrotreated light - (64742-49-0)	> 5,000.00, Rat - Category: NA	> 2,000.00, Rabbit - Category: NA	No data available.	No data available.	No data available.
Butane - (106-97-8)	No data available.	No data available.	658.00, Rat - Category: NA	No data available.	No data available.
Isobutane - (75-28-5)	No data available.	No data available.	658.00, Rat - Category: NA	No data available.	No data available.
N-Butyl Acetate - (123-86-4)	10,760.00, Rat - Category: NA	17,600.00, Rabbit - Category: NA	No data available.	No data available.	No data available.
Stoddard solvent - (8052-41-3)	> 5,000.00, Rat - Category: NA	No data available.	No data available.	5.50, Rat - Category: NA	No data available.
2-Methoxy-1-Methylethyl Acetate - (108-65-6)	5,155.00, Rat - Category: NA	> 2,000.00, Rabbit - Category: NA	No data available.	No data available.	No data available.

Carcinogen Data

CAS No.	Ingredient	Source	Value
67-64-1	Acetone	OSHA	Regulated Carcinogen: No;
		NTP	Known: No; Suspected: No;
		IARC	No
		ACGIH	A4
74-98-6	Propane	OSHA	Regulated Carcinogen: No;
		NTP	Known: No; Suspected: No;
		IARC	No



Safety Data Sheet

SO SURE General Purpose Enamel, Green 14064

Revision Date:
13 August, 2026

		ACGIH	No Established Limit
75-28-5	Isobutane	OSHA	Regulated Carcinogen: No;
		NTP	Known: No; Suspected: No;
		IARC	No
		ACGIH	No Established Limit
106-97-8	Butane	OSHA	Regulated Carcinogen: No;
		NTP	Known: No; Suspected: No;
		IARC	No
		ACGIH	No Established Limit
108-65-6	2-Methoxy-1-Methylethyl Acetate	OSHA	Regulated Carcinogen: No;
		NTP	Known: No; Suspected: No;
		IARC	No
		ACGIH	No Established Limit
123-86-4	N-Butyl Acetate	OSHA	Regulated Carcinogen: No;
		NTP	Known: No; Suspected: No;
		IARC	No
		ACGIH	No Established Limit
8052-41-3	Stoddard solvent	OSHA	Regulated Carcinogen: No;
		NTP	Known: No; Suspected: No;
		IARC	No
		ACGIH	No Established Limit
64742-49-0	Naphtha (petroleum), hydrotreated light	OSHA	Regulated Carcinogen: No;
		NTP	Known: No; Suspected: No;
		IARC	No
		ACGIH	No Established Limit

Classification	Category	Hazard Description
Acute toxicity (oral)	---	Not Applicable
Acute toxicity (dermal)	---	Not Applicable
Acute toxicity (inhalation)	---	Not Applicable
Skin corrosion/irritation	---	Not Applicable
Serious eye damage/irritation	2A	Causes serious eye irritation.
Respiratory sensitization	---	Not Applicable
Skin sensitization	---	Not Applicable
Germ cell mutagenicity	---	Not Applicable
Carcinogenicity	---	Not Applicable
Reproductive toxicity	---	Not Applicable
STOT-single exposure	---	Not Applicable
STOT-single exposure (3)	3	May cause drowsiness or dizziness.
STOT-repeated exposure	1	Causes damage to organs through prolonged or repeated exposure.
Aspiration hazard	---	Not Applicable



Safety Data Sheet

SO SURE General Purpose Enamel, Green 14064

Revision Date:
13 August, 2026

Possible routes of entry:

Inhalation, ingestion, skin contact, and skin absorption.

Symptoms and effects, both acute and delayed:

EFFECTS OF OVEREXPOSURE: Overexposure may result in light-headedness, staggering gait, giddiness, and possible nausea. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. May cause eye and skin irritation. SIGNS AND SYMPTOMS OF OVEREXPOSURE: Headache, dizziness, nausea, and loss of coordination are indications of excessive exposure to vapors or spray mists. Redness and itching or burning sensation may indicate eye or excessive skin exposure. MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: Pre-existing respiratory, skin, and eye disorders. No chronic toxicity or long term toxicity information available. Treat symptomatically.

Inhalation May cause drowsiness or dizziness.

Eyes Causes serious eye irritation.

Section 12. Ecological information

Toxicity

No additional information provided for this product. See Section 3 for chemical specific data.

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/L	48 hr EC50 crustacea, mg/L	ErC50 algae, mg/L
Acetone - (67-64-1)	8,120.00, Pimephales promelas	8,800.00, Daphnia pulex	7,000.00, Pseudokirchneriella subcapitata
Propane - (74-98-6)	49.90, Fish	69.43, Daphnia sp	19.37, Algae
Naphtha (petroleum), hydrotreated light - (64742-49-0)	No data available.	2.60, Chaetogammarus marinus	No data available.
Butane - (106-97-8)	49.90, Fish (Piscis)	69.43, Daphnia sp	19.37, Algae
Isobutane - (75-28-5)	No data available.	No data available.	No data available.
N-Butyl Acetate - (123-86-4)	18.00, Pimephales promelas	44.00, Daphnia sp	246.00, Pseudokirchnerella subcapitata
Stoddard solvent - (8052-41-3)	No data available.	No data available.	No data available.
2-Methoxy-1-Methylethyl Acetate - (108-65-6)	161.00, Pimephales promelas	501.00, Daphnia magna	> 1,000, Pseudokirchnerella subcapitata

Persistence and degradability

There is no data available on the preparation itself.

Bioaccumulative potential

Not Available

Mobility in soil

No data available.

Results of PBT and vPvB assessment

This product contains no PBT/vPvB/vPvM chemicals.



Safety Data Sheet

SO SURE General Purpose Enamel, Green 14064

Revision Date:
13 August, 2026

Other adverse effects

No data available.

Section 13. Disposal considerations

Waste treatment methods

Waste should not be released to sewers. Observe all federal, state, and local regulations when disposing of this substance.

Section 14. Transport information



	DOT (Domestic Surface Transportation)	IMO / IMDG (Ocean Transportation)	ICAO/IATA
UN number	UN1950	UN1950	UN1950
UN proper shipping name	UN1950, Aerosols, Limited Quantity, 2.1,	Aerosols, Limited Quantity	Aerosols, Limited Quantity
Transport hazard class(es)	Class: 2.1 Sub Class: Not Applicable	Class: 2.1 Sub Class: Not Applicable	Class: 2.1 Sub Class: Not Applicable
Packing group	Not Applicable	Not Applicable	Not Applicable
Environmental hazards	IMDG Marine Pollutant: No;		
Special precautions for user	Not Applicable		

Section 15. Regulatory information

Regulatory Overview The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented.

Classification of the substance or mixture under OSHA's Hazard Communication Standard (1910.1200) revised 2024 (GHS revision 7).



Safety Data Sheet

SO SURE General Purpose Enamel, Green 14064

Revision Date:
13 August, 2026

Toxic Substance Control Act (TSCA)

CAS Number	Ingredient	Toxic Substance Control Act (TSCA)	Comments	Status
0000108-65-6	2-Methoxy-1-Methylethyl Acetate	Yes	PMN	ACTIVE
0000067-64-1	Acetone	Yes		ACTIVE
0000106-97-8	Butane	Yes		ACTIVE
0000075-28-5	Isobutane	Yes		ACTIVE
0000123-86-4	N-Butyl Acetate	Yes		ACTIVE
0064742-49-0	Naphtha (petroleum), hydrotreated light	Yes	UVCB	ACTIVE
0000074-98-6	Propane	Yes		ACTIVE
0008052-41-3	Stoddard solvent	Yes	UVCB	ACTIVE

EPCRA 302 Extremely Hazardous:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

EPCRA 313 Toxic Chemicals:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Carcinogens (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Developmental Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Female Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Male Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 Label Warning:

This product contains no chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

Section 16. Other information

Revision Date 13 August, 2026

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H220 Extremely flammable gas.

H224 Extremely flammable liquid and vapor.

H225 Highly flammable liquid and vapor.

H226 Flammable liquid and vapor.



Safety Data Sheet
SO SURE General Purpose Enamel,
Green 14064

Revision Date:
13 August, 2026

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H319 Causes serious eye irritation.

H336 May cause drowsiness and dizziness.

H372 Causes damage to organs through prolonged or repeated exposure.

IMPORTANT NOTE: This information is furnished without warranty, expressed or implied, as to accuracy or completeness. The information is obtained from various sources including the manufacturer and other third party sources. The information may not be valid under all conditions nor if this material is used in combination with other materials or any process. Final determination of suitability of any material is the sole responsibility of the user.

End of Document